



CPT SKID

With HYSON® 100 kN or 200 kN static cone penetrometer

Features:

- Ergonomic design
- Easy-to-operate
- Low noise diesel engine
- Suitable for electric or mechanical CPT testing

CPT SKID with HYSON® 100 kN or 200 kN static cone penetrometer

Introduction

Besides our mobile and lightweight hydraulically driven CPT rigs, skid mounted types have been developed for barges or vessels in offshore or near-shore applications.

In special cases they can be mounted on a crawler or other vehicles. The specifications of the rigs are similar to the mobile systems; mounted in a modified sea-freight container operators and equipment are protected from harsh weather conditions.

*"Van den Berg
in
every field"*

Specifications

	HYSON® 100 kN		HYSON® 200 kN	
	Nominal	Maximum	Nominal	Maximum
Pushing capacity	100 kN	125 kN	200 kN	250 kN
	(11 US tons)	(14 US tons)	(22 US tons)	(28 US tons)
Pulling capacity	130 kN	160 kN	260 kN	320 kN
	(15 US tons)	(18 US tons)	(29 US tons)	(36 US tons)
Pushing speed	2.0 cm/s	±14 cm/s	2.0 cm/s	±9.8 cm/s
Pulling speed	1.6 cm/s	±9.0 cm/s	1.6 cm/s	±5.2 cm/s

We reserve the right to change specifications without notice.



A.P. van den Berg Machinefabriek B.V.

IJzerweg 4, P.O. Box 68
8440 AB Heerenveen, The Netherlands
Phone +31 (0)513 63 13 55
Fax +31 (0)513 63 12 12
E-mail apb@apvdberg.nl
<http://www.apvdberg.nl>

A.P. van den Berg, Inc.

P.O. Box 654, 109 Greenwood Circle
Milford, PA 183 USA
Phone +1 570 296 8224
Fax +1 570 296 4886
E-mail apvdberg@ptd.net