



a.p. van den berg
The CPT factory

ROSON 100

the versatile and full force seabed CPT system



features

- compact & proven wheel drive system with a pushing force of 100 kN
- deployable from medium vessel, also available in a near-shore configuration
- 1,500 m water depth rating, CPT depth up to 50 m
- suitable for 5, 10 & 15 cm² Icones & click-on modules
- suitable for Seabed Sampler XL
- software for realtime data acquisition and control

creating tools that move your business

ROSON 100, the versatile and full force seabed CPT system



introduction

The ROSON is a proven seabed CPT system, deployed from a vessel with an A-frame or crane through a moon pool or over the side. The electrical wheel drive system pushes the pre-assembled CPT string into the seabed. Wheel friction is imposed by hydraulic force. A self-tensioning electric winch with heave

compensation feeds the umbilical for power supply and data communication.

versatile, full force & easy maintainability

The versatile ROSON 100 is capable of performing CPTs and taking soil samples at water depths up to 1,500 m. It can be used in projects where a pushing force of up to 100 kN is required. A CPT depth up to 50 m is achievable (of course depending on the soil conditions and reaction force). The versatile design makes this ROSON also very suitable as near shore solution for water depths ranging from 30 to 250 m. To limit the required investment, the self-tensioning winch is not applied for this near shore ROSON and data communication runs over a direct cable to the Icontrol data logger on the vessel. The ROSON 100 is easy to maintain by mounting the drive units on one side of the frame. There is enough space for feeding and removing measuring instruments. Furthermore it is easy to check and adjust components. Both drive wheels are identical and can be rapidly exchanged for maintenance.

Specifications drive unit

Water depth rating	1,500 m
Driving speed	20 mm/sec
Pushing/pulling force	100 kN
Electrical motors	2 x 1.5 kW
Wheel diameter	Ø 1,000 mm

Specifications seabed frame

Footprint	2,500 x 2,500 mm ²
Height	2,300 mm
Lifting point height	2,900 mm
Weight	7,000 kg in air (excl. ballast)
Guiding masts	included

digital Icone data acquisition system

The ROSON works in conjunction with A.P. van den Berg's digital Icone data acquisition system, consisting of the Icontrol, Icones and the Ifield software for realtime data presentation. It enables measurement of cone resistance (q_c), local friction (f_s), pore water pressure (u) and inclination (lx/y). The Icone is easily extendable with click-on modules to measure other than the four standard parameters. The modules Conductivity, Magneto, Vane and Seismic are available for the ROSON.

Specifications CPT with the ROSON 100

Icone sizes/type	5, 10 & 15 cm ² / CPT or CPTU
Icone modules	
- up to 1,500 m water depth	Vane
- up to 1,000 m water depth	Seismic, Conductivity & Magneto
CPT string diameter	Ø 25 or Ø 36 mm

sampling with the Seabed Sampler XL

In combination with the Seabed Sampler XL it is possible to take high quality seabed samples with a diameter of 110 mm and a length up to 20 m. The recovery ratio is higher than 95%, which means that very little disturbance occurs to the sample. Sample tubes are pre-assembled in the ROSON. Then the total assembly is lowered to the seabed and the sample string is pushed into the soil by means of the ROSON drive wheels.

Specifications Seabed Sampling with the ROSON 100

Sample diameter	110 mm
Sample length	up to 20 m
Water depth	max. 1,500 m
Recovery ratio	higher than 95%



A.P. van den Berg Ingenieursburo bv

IJzerweg 4, 8445 PK
P.O. Box 68, 8440 AB
Heerenveen, The Netherlands
tel : +31 (0)513 63 13 55
fax: +31 (0)513 63 12 12
www.apvandenber.com
info@apvandenber.com



We reserve the right to change specifications without prior notice.
ROSON and Icone are trademarks of A.P. van den Berg, Heerenveen.