

# Optocone

starting a new era in CPT data acquisition



## features

- wireless
- reliable and accurate
- easy-to-use
- time-saving



## Optocone, starting a new era in CPT data acquisition

#### wireless CPT

It is possible to replace the awkward measuring cable by a reliable wireless system for electrical cone testing. The system ensures more convenient CPT operations and higher producti-ons. And moreover – ever thought of mechanical automation of rod handling? A piece of cake now that the cable is out of the way! See leaflet S<sub>3</sub>8 AUTOCOSON for more information.



### description

The system consists of an adapter piece which is connected on top of the electrical cone, very much like the usual screw-thread adapter. The adapter piece contains all electronics for optical data transmission of 6 soil parameters and a non-vo-latile memory for backup data. A data scan is made 5 times per second, which is transmitted to a camera installed over the upperbeam of the CPT unit through a light transducer in the CPT rod. When placing the CPT rods the light transducers are positioned on top of each other without having to be con-nected. The camera transmits the data to the data acquisition system where it is immediately stored and shown on screen. By means of an optical transmitter, commands can be sent to the cone from the data acquisition system. Data transmission can be interrupted for ± 8 seconds for adding on new CPT rods, without loss of data on the screen.

#### main features

- optical transducer data transmission
- memory inside the adaptor for wireless testing and back-up data
- possibility for automated rod handling

### compatibility

- suitable for all onshore (electrical) CPT units
- suitable for all A.P. van den Berg standard electrical cones
- existing CPT units can be adapted
- existing cones can be adapted

#### special applications

The Optocone is ideally suited for special applications, like the Drilling Rig Conversion Kit (see leaflet S20), where the CPT pushing piece with integrated camera are used to perform CPT's with a drilling rig. The required pushing capacity is sup-plied by the drilling rig's travelling table. Another application is wireless cone pentration testing with the HYSON 100 kN-LW lightweight, single-cylinder CPT unit (see leaflet S05). Elimina-tion of the cable makes electrical CPT's with this type of equip-ment much more convenient.



### specifications

- data acquistion of the parameters: cone tip resistance, local friction or cone tip resistance + local friction, porewater pressure, inclination
- resolution cone tip resistance, local friction, cone tip resistance + local friction and pore-water pressure : 16 bits
- resolution inclination and inclination X-Y: 8 bits
- measuring depth can be extended with optional repeaters
- scanning rate 5 scans/s
- scanning rate of the non-volatile memory 1 scan/s up to 7,5 hrs
- diameter of the adaptor piece Ø36 mm
- data storage in ASCII or GEF format

#### A.P. van den Berg

Komeet 34, 8448 CG Heerenveen P.O. Box 68, 8440 AB Heerenveen The Netherlands

tel: +31 (0)513 63 13 55 info@apvandenberg.com www.apvandenberg.com



We reserve the right to change specifications without prior notice. Optocone, AUTOCOSON and HYSON are trademarks of A.P. van den Berg, Heerenveen. A.P. van den Berg Machinefabriek is a tradename of A.P. van den Berg Ingenieursburo bv.